



CASCADE

LED

A range of linear wallwashers utilising LED technology and bespoke reflector optics providing a striation free distribution. Designed for exposed T, plasterboard or spring T ceilings. Surface mounting options are available to special order.

- Specially designed optic provides light close to the horizontal thus reducing shadow lines at the top of the wall or display.
- Colour rendering index Ra >80.
- Predicted lifetime >50,000 hours.
- Colour temperature – available in 3000K and 4000K versions.
- Photometric data available in Eulumdat format on request or via Relux website.
- No ultra violet or infra red emissions.
- Standard ITAB Prolight LED warranty (see page 161).



Catalogue No.	Mounting	Nominal Length (mm)	LED Flux (Lumens)	Luminaire Flux (Lumens)	LED Wattage	Total System Wattage	Luminaire Lumens / Circuit Watt	Colour Temp	CRI
CSC/06/F/30/4K/XT	Exposed T	600x300	3000	2297	16.6	19.9	115.4	4000K	>80
CSC/06/F/40/4K/XT	Exposed T	600x300	4000	3062	23.3	26.2	116.9	4000K	>80
CSC/12/F/60/4K/XT	Exposed T	1200x300	6000	4593	33.3	37.6	122.2	4000K	>80
CSC/12/F/80/4K/XT	Exposed T	1200x300	8000	6124	46.6	53.3	114.9	4000K	>80

For colour 3000 Kelvin, replace '4K' in the catalogue number with '3K': e.g. CSC/06/F/30/3K
Dimmable Drivers: To specify DALI driver, replace 'F' in the catalogue number with 'X': e.g. CSC/06/X/30/4K
 To specify DALI driver wired for Switchdim operation, replace 'F' in the catalogue number with 'S': e.g. CSC/06/S/30/4K
 For **Plasterboard** version, replace 'XT' in the catalogue number with 'PB': e.g. CSC/06/F/30/4K/PB
 For **Spring T** version, replace 'XT' in the catalogue number with 'XB': e.g. CSC/06/F/30/4K/XB

