



Ultra White



Ultra Grey



Ultra Black



Ultra Mini White




Ultra Mini Grey




Ultra Mini Black

ULTRA/ULTRA MINI LED

- Die cast aluminium track mounted spotlights.
- Ultra ~ 3000 lumens (luminaire output).
- Ultra Mini ~ 1400 lumens (luminaire output).
- Interchangeable optics, available in spot, medium, flood (Ultra and Ultra Mini) and wide flood option (Ultra only).
- Universal 3 circuit track adaptor.
- Colour temperature – available in 3000K and 4000K versions.
- Colour rendering index = 90+
- Finished in white as standard, also available in black or grey.
- Predicted lifetime > 50,000 hours.
- No ultra violet or infra red emissions.
- Photometric data available in Eulumdat format on request or via Relux website.
- Standard ITAB Prolight LED warranty.



Ultra



Ultra Mini

Catalogue No.	Housing	Colour	Distribution	Luminaire Flux (Lumen)	Total System Wattage	Luminaire Lumens / Circuit Watt	Colour Temp	CRI	Weight (Kg)
NOR/265-500-10-3K	Ultra	White	Spot (14)	2900	30	97	3000K	90+	1.2
NOR/265-500-20-3K	Ultra	Black	Spot (14)	2900	30	97	3000K	90+	1.2
NOR/265-500-30-3K	Ultra	Grey	Spot (14)	2900	30	97	3000K	90+	1.2
NOR/265-501-10-3K	Ultra	White	Medium (28)	2900	30	97	3000K	90+	1.2
NOR/265-501-20-3K	Ultra	Black	Medium (28)	2900	30	97	3000K	90+	1.2
NOR/265-501-30-3K	Ultra	Grey	Medium (28)	2900	30	97	3000K	90+	1.2
NOR/265-502-10-3K	Ultra	White	Flood (39)	2900	30	97	3000K	90+	1.2
NOR/265-502-20-3K	Ultra	Black	Flood (39)	2900	30	97	3000K	90+	1.2
NOR/265-502-30-3K	Ultra	Grey	Flood (39)	2900	30	97	3000K	90+	1.2
NOR/265-503-10-3K	Ultra	White	Wide Flood (54)	2900	30	97	3000K	90+	1.2
NOR/265-503-20-3K	Ultra	Black	Wide Flood (54)	2900	30	97	3000K	90+	1.2
NOR/265-503-30-3K	Ultra	Grey	Wide Flood (54)	2900	30	97	3000K	90+	1.2
NOR/277-500-10-3K	Ultra Mini	White	Spot (18)	1400	13	108	3000K	90+	0.8
NOR/277-500-20-3K	Ultra Mini	Black	Spot (18)	1400	13	108	3000K	90+	0.8
NOR/277-500-30-3K	Ultra Mini	Grey	Spot (18)	1400	13	108	3000K	90+	0.8
NOR/277-501-10-3K	Ultra Mini	White	Medium (31)	1400	13	108	3000K	90+	0.8
NOR/277-501-20-3K	Ultra Mini	Black	Medium (31)	1400	13	108	3000K	90+	0.8
NOR/277-501-30-3K	Ultra Mini	Grey	Medium (31)	1400	13	108	3000K	90+	0.8
NOR/277-502-10-3K	Ultra Mini	White	Flood (42)	1400	13	108	3000K	90+	0.8
NOR/277-502-20-3K	Ultra Mini	Black	Flood (42)	1400	13	108	3000K	90+	0.8
NOR/277-502-30-3K	Ultra Mini	Grey	Flood (42)	1400	13	108	3000K	90+	0.8

Colour Temperature: To specify 4000K colour temperature, replace '3K' in the catalogue number with '4K': e.g. NOR/265-501-10-4K